P82C – 3/2 Control Valve Excelon® Plus Modular System



- Port size: 1/4" to 3/8" (ISO G/PTF)
- Excelon® Plus design allows in-line installation or modular installation with other Excelon® Plus products
- High forward flow capacity
- 3 port/2 position valve, normally closed
- High flow dump facility
- Solenoid and air pilot options

Technical features

Medium:
Compressed air only

Maximum supply pressure:
145 psi (10 bar)

Minimum operating pressure:
43 psi (3 bar)

Air Pilot pressure must be equal to or greater than the supply pressure.



Port size:
G1/4, G3/8, 1/4 PTF, 3/8 PTF

Flow:
43 scfm (20 dm^3/s) at port size 1/4"
Full flow P1 to P2 @ 91 psi (6.3 bar) inlet, with 7 psi (0.5 bar) pressure drop
P2 to P3 = 43 scfm (20 dm^3/s)

Ambient/Media temperature:
-4 to +149°F (-20 to +65°C)
Air supply must be dry enough to avoid ice formation at temperatures below +35°F (+2°C).

Materials:
Body: Aluminum
End Caps: Aluminum
Body covers: ABS
Elastomers: NBR
Valve: Brass
Air Pilot: Aluminum

Technical data P82C

Symbol	Port Size (PTF)	Function	Voltage	Exhaust Port (PTF)	Weight lbs (g)	Model
	1/4	Solenoid/spring	24 VDC	1/4	0.98 (444)	P82C-2AT-PFA
	3/8	Solenoid/spring	24 VDC	1/4	0.98 (444)	P82C-3AT-PFA
	1/4	Air/spring	NA	1/4	0.98 (444)	P82C-2AA-NNN
	3/8	Air/spring	NA	1/4	0.98 (444)	P82C-3AA-NNN

Electrical details for solenoid operators

Voltage tolerance:	-10%/+15%
Rating:	100% continuous duty
Inlet orifice:	0.8mm
Electrical connection:	15mm DIN EN 175301-803 (DIN 43 50) Table C
Manual override:	Shrouded push button, spring return
Protection class:	IP65 with sealed plug (ISO 6952) NEMA 4
Materials:	PP5 (body), NBR (seals)

Voltage rating and spare coils

	Voltage	Power	Replacement
	24 VDC	1.2 W	840650-50KIT
	110 VAC	1.5 VA	840650-51KIT
	220 VAC	1.5 VA	840650-52KIT

Our policy is one of continued research and development. We therefore reserve the right to amend, without notice, the specifications given in this document. (2019 - 9261a) © 2020 IMI International s.r.o.

Option selector

P82C-★★★ – ★★★

Function	Substitute
3/2 Control Valve	C

Port Size	Substitute
1/4"	2
3/8"	3

Thread Form	Substitute
PTF	A
ISO G	G

Operator	Substitute
Air Pilot	A
Solenoid Operated	T


Connector	Substitute
With connector	A
none	N

Solenoid	Substitute
110/120 VAC	A
220/240 VAC	B
24 VDC	F
none	N


Solenoid Operator	Substitute
Non-Locking push button	P
none	N

Flow characteristics

Port size: 1/4"



Port size: 3/8"



Our policy is one of continued research and development. We therefore reserve the right to amend, without notice, the specifications given in this document. (2019 - 9261a) © 2020 IMI International s.r.o.

Accessories

Quikclamp®



820014-51KIT

Quikclamp® with bracket assembled



820014-52KIT

Pressure sensing block 1/4 PTF



820016-50KIT

Pressure sensing block G1/4



820016-51KIT

Full flow porting block 3/8 PTF




820028-50KIT

Full flow porting block G3/8




820028-53KIT

Port Adaptors 1/4 PTF




820015-02KIT

Port Adaptors 3/8 PTF




820015-03KIT

Port Adaptors G1/4



820015-08KIT

Port Adaptors G3/8



820015-09KIT

Air Pilot Operator 1/8 PTF



840623-50KIT

Air Pilot Operator 1/8 ISO G



840623-51KIT

Silencer

Heavy duty muffler, 1/4" NPT male thread, brass wire element



MB002A

Heavy duty muffler, R1/4 male thread, brass wire element



MB002B

Our policy is one of continued research and development. We therefore reserve the right to amend, without notice, the specifications given in this document. (2019 - 9261a) © 2020 IMI International s.r.o.

Accessories continued

Connection cable with plug, LED and M12 Female



Description	Cable length ft. (m)	Model
PUR-Cable; M12/valve type C DIN connector	1.97 (0.6)	NC-DINCA-123MS-A
	3.28 (1)	NC-DINCA-123MS-1
	6.56 (2)	NC-DINCA-123MS-2
	16.40 (5)	NC-DINCA-123MS-5

Plug with with moulded cable and indicator




Voltage	Cable length ft. (m)	Model
12 - 24 V a.c. / d.c	3.28 (1)	V10014-D01
12 - 24 V a.c. / d.c	9.84 (3)	V10014-D03
110 V a.c. / d.c.	3.28 (1)	V10015-D01
110 V a.c. / d.c.	9.84 (3)	V10015-D03
220 V a.c. / d.c	3.28 (1)	V10016-D01
220 V a.c. / d.c	9.84 (3)	V10016-D03

Plug with moulded cable



Description	Cable length ft. (m)	Model
3 pin plug with moulded cable	3.28 (1)	V10013-D01
3 pin plug with moulded cable	9.84 (3)	V10013-D03

Light Emitting Seals, 15mm form C



Description	Model
Light Emitting Seals Circuit A (12 - 24 V d.c.)	V10037-E13
Light Emitting Seals Circuit B (110 - 120 V a.c.)	V10037-E18
Light Emitting Seals Circuit B (220 - 240 V a.c.)	V10037-E19

Plug with cable gland and indicator



Description	Model
Plug with cable gland and indicator 12-24 V a.c. / d.c., c/w LED / VDR	V10012-D13
Plug with cable gland and indicator 110 V a.c. / d.c., c/w LED / VDR	V10012-D18
Plug with cable gland and indicator 220 V a.c. / d.c., c/w LED / VDR	V10012-D19

M12 Adaptor Top - MSUP Valve Plug Form C 8MM



7000-42831-0000000

M12 Adaptor Rear - MSUP Valve Plug Form C 8MM



7000-42811-0000000

Plug with cable gland




V10027-D00

Our policy is one of continued research and development. We therefore reserve the right to amend, without notice, the specifications given in this document. (2019 - 9261a) © 2020 IMI International s.r.o.

Dimensions in mm
Projection/Third angle


Dimensions




1 1/4" exhaust port (NPT or ISO G)

Our policy is one of continued research and development. We therefore reserve the right to amend, without notice, the specifications given in this document. (2019 - 9261a) © 2020 IMI International s.r.o.


Dimensions in inches (mm)
Projection/Third angle






Accessories

Quikclamp® with wall bracket



Quikclamp®



Our policy is one of continued research and development. We therefore reserve the right to amend, without notice, the specifications given in this document. (2019 - 9261a) © 2020 IMI International s.r.o.